

# Trojan® 製品カタログ
















A Comprehensive Battery Selection Guide



Made in USA

BCI グループ サイズ	タイプ	リザーブキャパシティ(RC)			容量(Ah)				電圧 (V)	端子形状	寸法(mm)			重量 (kg)	HydroLink™ or Single-Point Watering Kit
		@25 Amps	@56 Amps	@75 Amps	5 時間率	10 時間率	20 時間率	100 時間率			長さ	幅	高さ		
<b>6ボルト ディープサイクル液式バッテリー</b>															
GC2	T-105	447	—	115	185	207	225	250	6	1, 3, 4	262	181	283	28	HydroLink
GC2	T-105 Plus	447	—	115	185	207	225	250	6	1	262	181	281	28	—
GC2	T-125	488	—	132	195	221	240	266	6	1	262	181	283	30	HydroLink
GC2	T-125 Plus	488	—	132	195	221	240	266	6	1	262	181	281	30	—
GC2H	T-145	530	—	145	215	239	260	287	6	1, 4	262	181	303	33	HydroLink
GC2H	T-145 Plus	530	—	145	215	239	260	287	6	1	262	181	303	33	—
DIN	TE35	500	—	135	201	225	245	270	6	8	244	191	269	31	—
901	J250G	475	—	130	195	216	235	261	6	7	309	174	290	30	HydroLink
901	J250P	540	—	135	215	230	250	278	6	6	296	176	293	33	Single-Point
902	J305G-AC	678	—	175	258	290	315	350	6	4	314	174	366	40	HydroLink
902	J305P-AC	711	—	195	271	304	330	367	6	6	296	176	366	44	Single-Point
902	J305H-AC	781	—	215	295	331	360	400	6	6	296	176	366	45	Single-Point
903	L16P-AC	850	—	220	344	386	420	467	6	6	296	176	425	52	Single-Point
<b>8ボルト ディープサイクル液式バッテリー</b>															
GC8	T-875	295	117	—	145	155	170	189	8	1	260	180	283	29	HydroLink
GC8	T-890	340	132	—	155	175	190	211	8	1	260	180	283	31	HydroLink
<b>12ボルト ディープサイクル液式バッテリー</b>															
27	27TMH	200	—	51	95	106	115	128	12	7, 9	326	168	247	28	—
30H	30XHS	225	—	57	105	120	130	144	12	7, 8	354	171	256	30	—
GC12	T-1275	280	102	70	120	134	150	166	12	1	329	181	283	39	HydroLink
GC12	T-1275 Plus	280	102	70	120	134	150	166	12	1	329	181	272	39	—
GC12	J150	280	102	70	120	134	150	166	12	1	354	181	283	38	HydroLink
GC12	J150 Plus	280	102	70	120	134	150	166	12	1	354	181	283	38	—
921	J185P-AC	380	—	104	168	189	205	226	12	6	380	176	373	52	Single-Point
921	J185H-AC	440	—	121	185	207	225	249	12	6	380	176	373	56	Single-Point
921	J185HG-AC	440	—	121	185	207	225	249	12	7	391	175	372	56	HydroLink
<b>6ボルト ディープサイクル AGMバッテリー</b>															
GC2	T105-AGM	440	—	115	171	187	217	230	6	5, 8, 15	262	179	273	31	—
902	J305-AGM	670	—	185	250	273	310	329	6	5, 6, 15	296	176	358	43	—
903	L16-AGM	817	—	215	290	323	370	392	6	5, 6, 15	296	176	417	52	—
<b>シルバーライン ディープサイクル液式バッテリー</b>															
GC2	S-105	390	—	105	175	193	215	232	6	1	262	181	273	26	HydroLink
902	S-305	624	—	155	242	271	295	328	6	4	314	174	366	38	HydroLink
903	S-16	749	—	181	296	333	362	402	6	4	313	174	417	45	HydroLink
GC8	S-875	290	110	—	135	147	165	176	8	1	259	180	272	28	HydroLink
GC12	S-1275	260	90	60	113	126	145	155	12	1	329	181	272	35	HydroLink

## ●端子形状

							
<b>1 ELPT</b>	<b>2 EHPT</b>	<b>3 EAPT</b>	<b>4 EUT</b>	<b>5 LT</b>	<b>6 DT</b>	<b>7 UT</b>	<b>8 AP</b>
Embedded Low Profile	Embedded High Profile	Embedded Automotive Post	Embedded Universal	L-Terminal	Automotive Post & Stud	Universal	Automotive Post
							
<b>9 WNT</b>	<b>10 DWNT</b>	<b>11 ST</b>	<b>12</b>	<b>14 IND</b>	<b>15 M6/M8</b>	<b>16 SLT</b>	
Wingnut	Dual Wingnut	Stud	Cable & Plug	Industrial	6mm/8mm Insert	Small L-Terminal	

販売元



岡田商事株式会社 商事部

〒105-0012 東京都港区芝大門 1-3-7 4F

TEL.(03)5473-0371

FAX.(03)5473-0370

<http://www.okada-corp.com>